

Technical information (12/2021)

GRAVIHEL 1K PRE-FILL SPRAY

- The GRAVIHEL 1K pre-fill spray paint is prefilled with propellant gases and solvent and then filled by filling machines with the desired coat.
- Ideal for spot repairs or refinishing parts.
- A spray-like professional technique of spraying
- Aerosol can, maximum nominal volume 400 ml, filling quantity 100ml
- VOC compliant

VOC

2004/42/II B(e) (840) 839

EU limit value VOC for this type of product (category II B (e)) in the form, which is ready for application is 840 g/l. VOC of this product, prepared for use is 839 g/l.

		Clean the surface to be painted thoroughly with GRAVIHEL silicone cleaner. The area must be dry and free of dust and grease
	Shaking:	Shake can vigorously for 3 minutes
	Colour test:	The colour should be applied on to a piece of test cardboard to assess its suitability prior to application on the object
	Application:	Spray in several thin coats, from distance of approx. 25 cm.
	Drying time:	The drying time depends on the type of paint, thickness of a coat and temperature.
	Shelf life:	5 years

FOR PROFESSIONAL USE ONLY - See Safety Data Sheet

Contains: acetone, butan-1-ol. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with regional regulations. Buildup of explosive mixtures possible without sufficient ventilation.